

H94 DRIVE

LONG HAUL DRIVE

PIRELLI

TRUCK BUS AGRO OTR

FUEL EFFICIENCY AND HIGH MILEAGE FOR LONG HAUL SERVICE



HIGH
MILEAGE



HIGH
RETREADABILITY



ENERGY
EFFICIENCY



LOW
NOISE



PREMIUM PERFORMANCE

LONG TREAD LIFE AND LOW ROLLING RESISTANCE

The DLTC - Dual Layer Tread Compound together with extra-wide tread profile deliver the ideal performance balance between **long tread life** and **low rolling resistance**

FUEL EFFICIENCY AND DURABILITY

Specialized under-tread compound provide low rolling resistance and low heat generation, ensuring excellent retreadability



OUTSTANDING IN ALL WEATHER CONDITIONS

Unique tread pattern design combined with a full depth siping structure deliver **excellent grip** and **traction** in braking and acceleration throughout the life of the tire

TOP HANDLING IN A QUIET RIDE

Proprietary SATT structure combined with the unique tread pattern design deliver a unique driving experience for many miles spent in exceptional **acoustic comfort**

PROMETEAON

TECHNOLOGICAL FEATURES



DLTC

DUAL LAYER TREAD COMPOUND

High Silica Formulation Compound (Pirelli patent)

- Higher Mileage
- Low Rolling Resistance
- Excellent Grip
- Short Braking Distance



3SB



(Pirelli patent)

3 SANDWICH BELTS

- Enhanced Even Wear
- Extended Tire Life
- Great Retreadability
- Handling



HBW

HEXAGONAL BEAD WIRE

- High flexibility for easy mounting
- Bead thermal stability and durability
- Retreadability



RSR

ROTATED SHOULDER RIBS (Pirelli Patent)

Innovative shoulder tread contour allows correct distribution of footprint contact pressure

- Enhanced even wear
- High mileage



FRC

FULL RUBBERIZED CORDS

- Great Fatigue Resistance



BWC

BEAD WRAPPED CHAFER

- Increased Resistance
- Excellent Retreadability

H94 D SIZE RANGE

MAX TIRE LOAD

TIRE SIZE	PRODUCT NUMBER	LOAD RANGE PLY RATING	LOADED RADIUS IN. (MM)	OVERALL DIAMETER IN. (MM)	OVERALL WIDTH IN. (MM)	APPROVED RIMS IN.	MINIMUM DUAL SPACING IN. (MM)	REVS PER MILE RPM (RPK)	TREAD DEPTH 32NDS (MM)	MAX SPEED MPH (KPH)*	SINGLE LBS. PSL (KG KPA)	DUAL LBS. PSL (KG KPA)	TIRE WEIGHT LBS. (KG)	M+S
11R22.5	3756400	G/14	19.4	41.8	11.6	<u>8.25</u> , 7.50	12.5	500	26/32	81	6175/105	5840/105	143	✓
			(494)	(1061)	(295)		(318)	(311)	(20.5)	(130)	(2800/720)	(2650/720)	(65)	
295/75R22.5	3756300	G/14	18.9	40.6	11.4	<u>8.25</u> , 9.00	13.5	515.0	26/32	81	6175/110	5675/110	130	✓
			(479)	(1031)	(290)	<u>8.25</u> , 9.00	13.2	(320)	(20.5)	(130)	(2800/760)	(2575/760)	(59)	

* Exceeding the lawful speed limit is neither recommended nor endorsed.

Note: Rim underlined is measuring rim



June 2019 edition. Prometeon Tyre Group S.r.l. reserves the right to modify the contents of this publication without prior notice. Copyright (c) 2019 Prometeon Tyre Group S.r.l. The PIRELLI logo, SATT™ are trademarks used by Prometeon Tyre Group S.r.l. under license.

PROMETEON
DISCOVER MORE ON PROMETEON.COM