

H89 DRIVE Plus

LONG HAUL / SUPER-REGIONAL FUEL EFFICIENT DRIVE

PIRELLI

TRUCK BUS AGRO OTR

FUEL EFFICIENCY AND HIGH MILEAGE FOR LONG HAUL AND SUPER REGIONAL SERVICE



HIGH
MILEAGE



HIGH
RETREADABILITY



ENERGY
EFFICIENCY



LOW NOISE



PREMIUM PERFORMANCE

EXCELLENT PERFORMANCE IN ALL WEATHER CONDITIONS

Longitudinal and transversal groove geometry as well as casing dimensioning provide **excellent grip and traction** in braking and acceleration throughout the life of the tire

FUEL EFFICIENCY AND DURABILITY

New tread and base compounds deliver low rolling resistance and low heat generation, ensuring excellent retreadability and compliance with **EPA SmartWay®** verified fuel efficiency requirements



OUTSTANDING PRECISION AND DRIVING COMFORT

The optimized tread pattern geometry together with tread compound properties ensure **uniform wear** and **comfortable handling**

HIGH MILEAGE

Tire profile and the particular shoulder design prevent impact damage allowing a uniform distribution of torque across the footprint, resulting in even wear and **long tread life**

PROMETON

TECHNOLOGICAL FEATURES



DLTC

DUAL LAYER TREAD COMPOUND

High Silica Formulation Compound (Pirelli patent)

- Higher Mileage
- Low Rolling Resistance
- Excellent Grip
- Short Braking Distance



3SB

SATT

(Pirelli patent)

3 SANDWICH BELTS

- Enhanced Even Wear
- Extended Tire Life
- Great Retreadability
- Handling



HBW

HEXAGONAL BEAD WIRE

- High flexibility for easy mounting
- Bead thermal stability and durability
- Retreadability



RSR

ROTATED SHOULDER RIBS (Pirelli Patent)

Innovative shoulder tread contour allows correct distribution of footprint contact pressure

- Enhanced even wear
- High mileage



FRC

FULLY RUBBERIZED CORDS

- Great Fatigue Resistance



BWC

BEAD WRAPPED CHAFER

- Increased Resistance
- Excellent Retreadability

H89 DRIVE PLUS SIZE RANGE

| H89 DRIVE PLUS SIZE RANGE | | | | | | | | | | | MAX TIRE LOAD | | | | |
|---------------------------|----------------|-----------------------|------------------------|---------------------------|------------------------|-------------------|-------------------------------|-------------------------|------------------------|----------------------|------------------------------|----------------------------|-----------------------|----------|-----|
| TIRE SIZE | PRODUCT NUMBER | LOAD RANGE PLY RATING | LOADED RADIUS IN. (MM) | OVERALL DIAMETER IN. (MM) | OVERALL WIDTH IN. (MM) | APPROVED RIMS IN. | MINIMUM DUAL SPACING IN. (MM) | REVS PER MILE RPM (RPK) | TREAD DEPTH 32NDS (MM) | MAX SPEED MPH (KPH)* | SINGLE LBS. / PSI (KG / KPA) | DUAL LBS. / PSI (KG / KPA) | TIRE WEIGHT LBS. (KG) | SMARTWAY | M+S |
| 295/75R22.5 | 3756000 | G/14 | 18.9 | 40.6 | 11.4 | 8.25, 9.00 | 13.2 | 515 | 26/32 | 75 | 6175/110 | 5675/110 | 132 | ✓ | ✓ |
| | | | (479) | (1031) | (290) | | (335) | (320) | (20.5) | (120) | (2800/760) | (2575/760) | (60) | | |
| 11R22.5 | 3756200 | G/14 | 19.4 | 41.8 | 11.6 | 8.25, 7.50 | 12.5 | 500 | 26/32 | 75 | 6175/105 | 5840/105 | 141 | ✓ | ✓ |
| | | | (494) | (1061) | (295) | | (318) | (311) | (20.5) | (120) | (2800/720) | (2650/720) | (64) | | |

* Exceeding the lawful speed limit is neither recommended nor endorsed.

Note: Rim underlined is measuring rim



October 2019 edition. Prometeon Tyre Group S.r.l. reserves the right to modify the contents of this publication without prior notice. Copyright (c) 2019 Prometeon Tyre Group S.r.l. The PIRELLI logo, SATT™ are trademarks used by Prometeon Tyre Group S.r.l. under license.