

PREMIUM PERFORMANCE

CASING DURABILITY

Made possible by **3SB SATT Construction** in tread crown area, tread pattern with **stone ejectors in every groove** and **enhanced compound formulation in bead area** to improve heat dispersion to improve retreadibility.

FUEL EFFICIENCY

Delivered by improved tread compound designed to deliver EPA SmartWay verified Rolling Resistance compliance.



LONG TREAD LIFE

Enhanced by optimized tire profile, shoulder protection through support groove and innovative tread compound formulation.

STABLE HANDLING ON EVERY ROAD CONDITION

Granted by tread pattern with zig-zag groove design, M+S tread compound and 4 wide longitudinal grooves.



TECHNOLOGICAL FEATURES



DUAL LAYER TREAD COMPOUND

High Silica Formulation Compound (Pirelli patent)

- Higher Mileage
- Low Rolling Resistance
- Excellent Grip
- Short Braking Distance





FULL RUBBERIZED CORDS

- Great Fatigue Resistance



BEAD WRAPPED CHAFER

- Increased Resistance
- Excellent Retreadability

3SB

SATT() (Pirell

3 SANDWICH BELTS

- Enhanced Even Wear
- Extended Tire Life
- Great Retreadability
- Handling

MAX	TIRE	LOAD	

Tire Size		Load Range Ply Rating		Overall Diameter in. (mm)	Overall Width in. (mm)	Approved Rims in.	Minimum Dual Spacing in. (mm)	Revs Per Mile rpm (rpk)	Tread Depth 32nds (mm)	Max Speed mph (kph)	Single lbs. psi (kg kPa)	Dual lbs. psi (kg kPa)	Tire Weight Ibs. (kg)	M+S	SMARTWAY
295/75 R 22.5	3263700	G/14	18.4	39.5	11.3	<u>8.25</u> , 9.00	13.2	510	12/32	81	6175/110	5675/110	114.6	./	./
		3263700	G/14	(466.5)	(1004)	(288)		(335)	317	9.6	(130)	(2800/760)	(2575/760)	52	V

Note: Rim underlined is measuring rim





PROMETEON



